

# DEVELON DX17Z-7 1.7T TRACKED EXCAVATOR

## Details

**Price:** POA  
**Dealer Stock #:** DX17Z-1  
**New / Used:** Dealer New



## Seller Details

## Sales Representatives



Jacob

**Name:** DWL Machinery  
**Phone:** (02) 8311 1321  
**Dealer:** 8706626  
**License No:**  
**State:** NSW  
**Suburb:** Austral  
**Postcode:** 2179

## Description

FOLLOW US FOR ALL NEW LISTINGS: @dwlmachinery Ph: Andrew 0401 873 538 or 1300 DIAL DWL SPECIFICATIONS DIMENSION & WORKING RANGE ENGINE Make KUBOTA Model D902 Number of cylinders 3 Rated power, gross 16.2 hp (12.1 kW) @ 2400 rpm Rated power, net 16 hp (11.9 kW) @ 2400 rpm Max. torque, net 5.57 kgf.m @ 1900 rpm Displacement 0.898 l Bore and stroke 72 73.6 mm Starter 12 V, 1.2 kW Alternator 12 V, 40 A Air cleaner Double elements Unit DX17Z-7(Canopy) DX19-7(Cab) DX19-7(Canopy) Boom length mm 1750 1750 Arm length mm 1030 1230 1030 1230 Bucket capacity m<sup>3</sup> 0.04 0.04 Undercarriage (track + grouser) - Rubber Rubber Operating weight kg 1850 1980 1885 2020 Counterweight kg 180 260 A Overall length mm 3531 3528 3837 3835 C Overall width (track extension) mm 994 (1290) 994 (1290) Y Overall width (dozer blade) mm 1294 1294 B Overall height mm 2320 2275 2270 H Overall width of upper structure mm 980 980 I Overall height of canopy mm 2320 2275 2270 Ground clearance of counterweight mm 415 415 Overall height of engine hood mm 1095 1240 P Minimum ground clearance mm 150 150 Rear-end distance mm 645 720 1065 Rear-end swing radius mm 645 720 1065 J Distance between tumblers mm 1230 1230 K Undercarriage length mm 1580 1580 L Undercarriage width (track extension) mm 994 (1290) 994 (1290) M Track gauge (track extension) mm 764 (1060) 764 (1060) N Track shoe width mm 230 230 Q Height of blade mm 225 225 R Ground clearance of blade up mm 183 183 S Depth of blade down mm 222 222 Unit DX17Z-7 DX17Z-7 DX19-7 (Canopy) DX19-7 (Canopy) DX19-7 (Cab) Arm length mm 1030 1230 1030 1230 1230 1230 C Max. digging reach mm 3910 4100 3940 4130 4130 Max. digging reach (ground level) mm 3820 4010 3850 4040 4040 G Max. digging depth mm 2240 2440 2340 2540 2540 A Max. vertical wall depth mm 1750 1940 1840 2020 2020 E Max. digging height mm 3730 3870 3470 3585 3585 F Max. dumping height mm 2670 2810 2440 2550 2550 I Min. swing radius mm 1580 1645 1725 1760 1760 Boom swing angle (left/right) 55 / 59 55 / 59 55 / 59 MACHINE DIMENSIONS DRIVE SYSTEM Travel speed (low high) 2.06 3.73 km/h Traction force, max. (drawbar pull) 14.13 Kn Max. Gradeability 35 REFILL CAPACITIES DX17Z-7 DX19-7 Fuel tank 19.5 l 21.3 l Cooling system (radiator capacity) 5.4 l Engine oil 3.7 l Travel device 2 0.33 l Hydraulic tank 12.1 l 20 l HYDRAULICS Main pumps 2 17.3 l/min @ 2300 rpm Pilot pump (gear design) 10.4 / 6.2 l/min @ 2300 rpm Relief pressure aux. line 206 bar MAXIMUM SYSTEM PRESSURE Boom/arm/bucket (normal mode) 210 kg/cm<sup>2</sup> Swing (crossover relief) 165 kg/cm<sup>2</sup> SWING MECHANISM Swing speed 9.2 rpm Swing torque 4025 lbf.ft. (557 kgfm) ENVIRONMENT Sound level (ISO 6395) 92 dB(A)

## Product Details

<b>Type</b>	Dealer New
<b>Make</b>	Develon
<b>Model</b>	DX17-Z
<b>Registration Date</b>	8 April 2026

## Further Details

<b>configuration</b>	Std Excav Boom
<b>Excav Config</b>	Std Excav Boom
<b>Item</b>	New
<b>Condition</b>	
<b>Total Eng Power</b>	16
<b>Excav Size</b>	1
<b>Engine Make</b>	Develon
<b>Transmission</b>	n/a
<b>External Colour</b>	Orange
<b>Warranty</b>	Enquire

