

# DEVELON DX62Z-7 6.2T TRACKED EXCAVATOR

## Details

**Price:** POA  
**Dealer Stock #:** DX62Z-1  
**New / Used:** Dealer New



## Seller Details

## Sales Representatives



Jacob

**Name:** DWL Machinery  
**Phone:** (02) 8311 1321  
**Dealer:** 8706626  
**License No:**  
**State:** NSW  
**Suburb:** Austral  
**Postcode:** 2179

## Description

FOLLOW US FOR ALL NEW LISTINGS: @dwlmachinery Ph: Andrew 0401 873 538 or 1300 DIAL DWL SPECIFICATIONS DIMENSION & WORKING RANGE MACHINE DIMENSIONS WORKING RANGE ENGINE Model Develon D24 Number of cylinders 4 Rated power at 2200 rpm SAE J1995 44.3 kW (65 hp) Max. torque at 1600 rpm 260 Nm Idle (low - high) 1000 - 2300 rpm Displacement 2392 cm3 Bore stroke 90 mm 94 mm Starter 12 V / 2.5 kW Batteries - Alternator 1 12 V, 100 Ah 12 V, 90 A Air filter Double element air cleaner DRIVE SYSTEM Travel speed (low - high) 2.8 - 4.7 km/h Maximum traction 4.58 t Maximum gradeability 35 / 70% SWING MECHANISM Maximum swing speed 9.8 rpm Maximum swing torque 1380 kgfm HYDRAULICS Main pump 144.9 l/min DX62R-7 DX63-7 Implement 280 kgf/cm2 Travel 280 kgf/cm2 Swing 220 kgf/cm2 Unit DX50Z-7M DX55R-7M Boom type mm 2900 2900 Arm type mm 1900 1900 Bucket capacity m3 0.175 0.175 Undercarriage (track + grouser) - Rubber Rubber L1 Overall length mm 5631 5571 H1 Overall height Boom mm 2385 Cab mm 2575 W1 Overall width mm 1980 R1 Rear swing radius mm 1180 1350 H2 Ground clearance mm 208 L2 Rear end distance mm 1180 1350 W2 House width mm 1750 W3 Cab width mm 1150 H3 Height over cover mm 1588 H4 Counterweight clearance mm 628 A1/ A2 Boom swing angle (left/right) 60/53 H5 Track height mm 562 L3 Track length mm 2486 L4 Tumbler distance mm 1990 W4 Track gauge mm 1580 W5 Undercarriage width mm 1980 W6 Shoe width mm 400 etc. Grouser height mm 20 H6 Dozer digging depth mm 460 H8 Dozer lift clearance mm 488 H9 Dozer blade height mm 410 L8 Distance to dozer end mm 1840 Unit DX62R-7 DX63-7 Boom length mm 2900 2900 Arm length mm 1900 1600 1900 1600 Bucket capacity m3 0.175 0.175 A Max. digging reach mm 6610 6310 6440 6140 B Max. digging reach (ground) mm 6485 6175 6315 6005 C Max. digging depth mm 4095 3795 4095 3795 D Max. dumping height mm 4270 4040 4270 4040 E Min. swing radius mm 2850 2685 2680 2515 F Max. digging height mm 6025 5790 6025 5790 G Max. bucket pin height mm 5155 4925 5155 4925 H Max. vertical wall depth mm 2580 2380 2580 2380 I Max. radius vertical mm 5155 4935 4985 4765

## Product Details

|                          |              |
|--------------------------|--------------|
| <b>Type</b>              | Dealer New   |
| <b>Make</b>              | Develon      |
| <b>Model</b>             | DX62Z        |
| <b>Registration Date</b> | 8 April 2026 |

## Further Details

|                        |                |
|------------------------|----------------|
| <b>configuration</b>   | Std Excav Boom |
| <b>Excav Config</b>    | Std Excav Boom |
| <b>Item</b>            | New            |
| <b>Condition</b>       |                |
| <b>Total Eng Power</b> | 65             |
| <b>Excav Size</b>      | 1              |
| <b>Engine Make</b>     | Develon        |
| <b>Transmission</b>    | n/a            |
| <b>External Colour</b> | Orange         |
| <b>Warranty</b>        | Enquire        |



dia/inline/28582